



Ankrit
Technologies GmbH

electrical safety for patients and employees

ISOMED 1-channel S-Video

Item no.: 06A0



A galvanically isolated S-video channel with Mini-DIN sockets for transmitting a S-video stream, Y/C.

S-VIDEO:

One S-video signal can be connected via the green input socket. The red S-video socket delivers the galvanically isolated output signal.

PRODUCT CONFORMITY

The product is in accordance with the regulation (EU) 2017/745 on medical devices, Article 19 and Annex IV, Directive 2011/65 / EU (RoHS), Article 13 and Annex VI.

QUALITY MANAGEMENT

Ankrit Technologies GmbH has a certified quality system according to ISO 9001:2015.

You need more information? We are happy to provide further assistance! **phone +49 (0)821.47 86 67 80**

**FEEL
FREE TO
CONTACT
US!**

POWER SUPPLY UNIT

Supply voltage	230V AC \pm 10 % 50/60 Hz
Power consumption	10 VA

VIDEO INPUT CHANNELS

Input impedance	75 Ω
Input voltage	1,0 Vpp
Coupling	AC

VIDEO OUTPUT CHANNELS

Output impedance	75 Ω
Amplification	1 at 75 Ω
Coupling	AC
Frequency response	20Hz to 9 MHz (-3dB)

ISOLATION

Creepage distance	8 mm
Dielectric strength	4000 Veff AC

GENERAL INFORMATION

Weight	1,45 kg
Size	240 x 157 x 48 mm
Protection class	I
Degree of protection	IP 30