



A galvanically isolated S-video channel with Mini-DIN socket for transmitting a S-video stream, Y/C, or a galvanically isolated video channel with BNC socket for transmitting a composite signal.

S-VIDEO:

A S-video signal can be connected via the green input socket. The red S-video socket delivers the galvanically isolated output signal.

OR BNC:

One video signal can be connected via the green input socket. The red BNC socket delivers the galvanically isolated output signal.

PRODUCT CONFORMITY

The product is in accordance with the regulation (EU) 2017/745 on medical devices, Article 19 and Annex IV, Directive 2011/65 / EU (RoHS), Article 13 and Annex VI.

QUALITY MANAGEMENT

Ankrit Technologies GmbH has a certified quality system according to ISO 9001:2015.

You need more information? We are happy to provide further assistance! **phone +49 (0)821.47 86 67 80**

**FEEL
FREE TO
CONTACT
US!**

POWER SUPPLY UNIT

Supply voltage	230V AC \pm 10 % 50/60 Hz
----------------	--------------------------------

Power consumption	10 VA
-------------------	-------

VIDEO INPUT CHANNELS

Input impedance	75 Ω
-----------------	-------------

Input voltage	1,0 Vpp
---------------	---------

Coupling	AC
----------	----

VIDEO OUTPUT CHANNELS

Output impedance	75 Ω
------------------	-------------

Amplification	1 at 75 Ω
---------------	------------------

Coupling	AC
----------	----

Frequency response	20Hz to 9 MHz (-3dB)
--------------------	----------------------

ISOLATION

Creepage distance	8 mm
-------------------	------

Dielectric strength	4000 Veff AC
---------------------	--------------

GENERAL INFORMATION

Weight	1,45 kg
--------	---------

Size	240 x 157 x 48 mm
------	-------------------

Protection class	I
------------------	---

Degree of protection	IP 30
----------------------	-------